

VT5520-120F

FEATURES

- Line load regulated (30mA self-adjusting output regardless of load size or input voltage fluctuations)
- High power factor (energy saving/cost effective)
- Use with Mercury or neon
- In line On/off switch
- Solid state technology
- 24" H-V Output Leads
- UL 2161 listed
- Ground connection via mounting foot and green wire
- Open circuit and overload will shut unit down




SPECIFICATIONS

Input Voltage	120VAC (+/-10%) 50/60 Hz
Input Current	0.35A rms
Power Factor	0.95 min.
Output Frequency	Variable
Output Voltage	0V-5,500V
Output Current	20mA
Operating Temperature	32°F to 104°F / 0°C to 40°C
Driving Distance* (Based on Standard 12mm tube. Deduct one foot from driving footages for each pair of electrodes.)	
Neon	1-13 ft (0.03-3.9 m)
Mercury	1-16 ft (0.03-4.9 m)

*See Ventex Luminous Tube Footage Chart for more information.

DIMENSIONS

Length (A)	4.9 in	12.4 cm
Width (B)	1.8 in	4.6 cm
Height (C)	1.4 in	3.6 cm
Mounting (D)	4.50 in	11.4 cm
Mounting (E)	0.75 in	1.9 cm
Weight	6.5 oz	184 g
Power Cord	18.0 in Flying Leads	
GTO Leads	18.0 in	45.7 cm



Exclusive: These units are protected by Ventex's patented protective circuitry to prevent false tripping due to capacitive current. Patent #5892646