

# SILICONE NEON BOOTS & CAPS

Easy Cap™ and Easy Boot™ silicone new electrode enclosures

## Specifications

Easy Cap™ and Easy Boot™ for GTO-15 and GTO-10 (14-18 AWG) 7 Series for 0.252" OD GTO

SKU	Description	Qty/bag	Qty/carton
88700	10mm ECDB 7-10 Black	100	500
88705	10mm ECS 7-10 Black	100	500
88710	12mm ECDB 7-12 Black	100	500
88715	12mm ECS 7-12 Black	100	500
88720	13mm ECDB 7-13 Black	100	500
88725	13mm ECS 7-13 Black	100	500
88730	15mm ECDB 7-15 Black	100	500
88735	15mm ECS 7-15 Black	100	500
88800	10mm ECDB 7-10 White	100	500
88805	10mm ECS 7-10 White	100	500
88810	12mm ECDB 7-12 White	100	500
88815	12mm ECS 7-12 White	100	500
88820	13mm ECDB 7-13 White	100	500
88825	13mm ECS 7-13 White	100	500
88830	15mm ECDB 7-15 White	100	500
88835	15mm ECS 7-15 White	100	500

Used by  
the world's  
largest POP  
manufacturers



Rated for  
15,000 Volts,  
7,500 Volts to the  
ground, maximum  
current 60 mA

UL Recognized  
(E129809)

Classified for UL 879  
Edition (E247018) as  
an enclosure system  
for dry and damp  
locations

Easy Cap™ and Easy Boot™ for GTO-15 (14 AWG) 8 Series for 0.311" OD GTO

SKU	Description	Qty/bag	Qty/carton
88770	13mm ECDB 8-13 Black	100	500
88775	13mm ECS 8-13 Black	100	500
88780	15mm ECDB 8-15 Black	100	500
88785	15mm ECS 8-15 Black	100	500
88870	13mm ECDB 8-13 White	100	500
88875	13mm ECS 8-13 White	100	500
88880	15mm ECDB 8-15 White	100	500
88885	15mm ECS 8-15 White	100	500

### SCAN HERE

for UL UTYA information or visit  
<https://ventextech.com/products/silicone-neon-boots-caps/>



ventextech.com  
803.794.8061  
3490 Venture Dr., San Angelo, TX 76905