

RESIN BOND ACRYLIC BONDING AGENT™

Use with our #25 Hypo Glue Applicator for acrylic plastic and sign trim in channel letters

Thin and fast setting creating a strong bond

Specifications

SKU	Quart	86900
	Gallon	86905
Working time	1-2 minutes	
Fixture time	2-10 minutes	
80% Strength	4 hours	
Applicator#	#25	
Shelf life unopened	Indefinite	
Shelf life opened (with top)	2-Indefinite weeks*	
UL file	E516868	

* Resin bond is a single component bonding agent. It will evaporate but not change its chemical makeup or effectiveness.

Before use:

1. Read the health and safety information on the container before using
2. Request a Safety Data Sheet and keep on file
3. Be sure surfaces to be bonded are clean and smooth
4. Always try a small test on scrap material before going into production

Cost-effective



Clear in color

Single-component (Methylene Chloride) based cement

Specifically designed to join acrylic plastic to acrylic plastic, acrylic plastic to sign trim (cellulose acetate butyrate), and changeable letter track to acrylic plastic

*Only ships via pallet/LTL.
Use #25 Hypo Glue Applicator with Resin Bond. Use on extruded acrylic track. For modified acrylic (DR) or polycarbonate, try Channel Bond Polycarbonate Bonding Agent™.*